

C-800 E3/L3 & L2



The C-800 E3/L3 tread pattern is designed to provide extended wear. The longer life helps reduce the total cost of ownership while increasing efficiency and productivity.

The C-800 L2's self-cleaning profile offers a large footprint providing flotation on soft surfaces. Durable nylon construction provides strength and resistance to impact damage.

C-800 E3/L3

- Durable Nylon Construction
- Flat Profile Increases Stability
- Rugged Tread Design Provides Increased Traction
- Chip and Chunk Resistance for long life

C-800 L2

- Large Footprint
- Flat Profile with Deep Lugs
- Long Lasting Tread Life
- Good Flotation on Soft Surfaces



C-800 E3/L3



C-800 L2



Tire Size	Ply Rating	Rim	Tire O.D.	Section Width	Tread Depth	Inflation @ 10 km/h (Loaders) Pressure	Inflation @ 50 km/h (Dumpers)	Load Capacity @ 10 km/h	Load Capacity @ 50 km/h	Tire Weight
			mm	mm	mm	bar	bar	kg	kg	kg
C-800 E3/L3										
17.5-25	16	14.00-25/1.5	1350	445	26	4.8	3.0	7300	4250	117.3
20.5-25	20	17.00-25/2.0	1490	520	29	4.5	3.3	9500	6000	173.6
23.5-25	20	19.50-25/2.5	1615	595	30	3.8	3.0	10900	7300	233.6
26.5-25	28	22.00-25/3.0	1750	675	35	4.8	3.5	15500	10000	379.1
29.5-25	28	25.00-25/3.5	1875	750	38	4.3	3.3	17500	11500	445.5

Tire Size	Ply Rating	Rim	Tire O.D.	Section Width	Tread Depth	Inflation Pressure	Load Capacity @ 10 km/h	Tire Weight
			mm	mm	mm	bar	kg	kg
C-800 L2								
17.5-25	16	14.00-25/1.5	1350	445	26	4.8	7300	93.6
20.5-25	16	17.00-25/2.0	1490	520	30	3.5	8250	133.6