



**IMPLEMENT
TIRES**

IMPLEMENT TIRES



AT 603



AT 603 is a bias agro-industrial tire for backhoe loaders, compact loaders and compact dumpers in digging and loading applications. AT 603 has been engineered to ensure great traction on drive wheels providing the best performance on and off the road. The AT 603 “special” version offers improved cut and chip resistance while the “HD” version is ideal for heavy-duty service.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
18"										
10.5/80 - 18	W 9	W 8; 9	274	907	405	2657	STD	10	TL	138 A6/131 A8
10.5/80 - 18	W 9	W 8; 9	274	907	405	2657	HD	10	TL	138 A6/131 A8
10.5/80 - 18	W 9	W 8; 9	274	907	405	2657	SPL	10	TL	138 A6/131 A8
12.5/80 - 18	W 9	11	308	987	438	2892	STD	12	TL	148 A6/142 A8
12.5/80 - 18	W 9	11	308	987	438	2892	SPL	12	TL	148 A6/142 A8
12.5/80 - 18	W 9	11	308	987	438	2892	STD	16	TL	154 A6/150 A8
12.5/80 - 18	W 9	11	308	987	438	2892	STD	18	TL	156 A6/150 A8

HD: Heavy Duty Version ①

SPL: Special Version ②

STD: Standard



AW 711



FREE ROLLING
APPLICATION



DURABILITY



HANDLING



FUEL ECONOMY



HIGH LOAD
CAPACITY



STUBBLE
RESISTANCE

AW 711 is an implement radial tire specially designed for modern farming, and suitable for general purpose applications. Thanks to its special tread compound, the AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
		Rec.	Alt.						
16.5" 340/60 R 16.5	145 A8/B	11	-	324	820	368	2476	-	STD
380/55 R 16.5	150 A8/B	12	11.75	360	830	372	2500	-	STD
18" 400/60 R18	159 A8/B	14	13	394	945	419	2807	-	STD
440/55 R 18	159 A8/B	14	13	410	945	432	2893	-	STD
19.5" 15 R 19.5	139 D	11.75	12.75	389	1019	452	3055	-	STD

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



AW 702



AW 702 has been developed for implement machinery and trailers in soil tillage and transport applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12"										
7.00 - 12	4.25	-	185	665	295	1948	STD	6	TL	101 A6/98 A8
10.0/80 - 12	9.00	7.0	264	710	313	2080	STD	8	TL	122 A6/116 A8
10.0/80 - 12	9.00	7.0	264	710	313	2080	STD	10	TL	126 A6/121 A8
10.0/80 - 12	9.00	7.0	264	710	313	2080	AB	10	TL	126 A6/121 A8
10.0/80 - 12	9.00	7.0	264	710	313	2080	SPL	10	TL	126 A6/121 A8
15.3"										
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	8	TT	124 A6/119 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	10	TT	128 A6/123 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	10	TL	128 A6/123 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	12	TT	132 A6/126 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	12	TL	132 A6/126 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	14	TT	136 A6/130 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	14	TL	136 A6/130 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	18	TL	142 A6/138 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	10	TT	137 A6/131 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	10	TL	137 A6/131 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	12	TT	141 A6/135 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	12	TL	141 A6/135 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	14	TT	145 A6/139 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	14	TL	145 A6/139 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	AB	14	TL	145 A6/139 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	16	TT	147 A6/141 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	18	TT	149 A6/145 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	18	TL	149 A6/145 A8
12.5/80 - 15.3	9.00	-	312	885	387	2593	STD	14	TT	147 A6/142 A8
12.5/80 - 15.3	9.00	-	312	885	387	2593	STD	14	TL	147 A6/142 A8
12.5/80 - 15.3	9.00	-	312	885	387	2593	STD	16	TT	150 A6/144 A8

AB: Aramid belted version
SPL: Special version ②
STD: Standard



AW 702



AW 702 has been developed for implement machinery and trailers in soil tillage and transport applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
16" 6.00 - 16	4.00 E	4.50 E; 4½ K	169	722	337	2150	STD	6	TT	101 A6/98 A8
6.00 - 16	4.00 E	4.50 E; 4½ K	169	722	337	2150	STD	6	TL	101 A6/98 A8
6.00 - 16	4.00 E	4.50 E; 4½ K	169	722	337	2150	STD	8	TT	110 A6/ 106 A8
10.50 - 16	6.00 T	-	305	975	445	2986	STD	14	TT	-
10.5/65 - 16	W 9	W 8; W 8 L	274	755	343	2112	STD	10	TT	129 A6/123 A8
10.5/65 - 16	W 9	W 8; W 8 L	274	755	343	2112	STD	10	TL	129 A6/123 A8
10.5/65 - 16	W 9	W 8; W 8 L	274	755	343	2112	SPL	10	TL	129 A6/123 A8
10.5/65 - 16	W 9	W 8; W 8 L	274	755	343	2112	STD	14	TT	137 A6/130 A8
10.5/65 - 16	W 9	W 8; W 8 L	274	755	343	2112	STD	14	TL	137 A6/130 A8
10.5/65 - 16	W 9	W 8; W 8 L	274	755	343	2112	IND	14	TL	137 A6/130 A8
13.0/55 - 16	11.0	-	336	770	345	2256	STD	12	TL	136 A6/133 A8
13.0/55 - 16	11.0	-	336	770	345	2256	STD	14	TL	139 A6/136 A8
13.0/55 - 16	11.0	-	336	770	345	2256	STD	18	TL	149 A6/146 A8
13.0/75 - 16	11.0	9; W 9; W 11	340	890	396	2726	STD	10	TL	142 A6/138 A8

IND: Industrial ①

SPL: Special version ②

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



AW 702



AW 702 has been developed for implement machinery and trailers in soil tillage and transport applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
18" 10.5/80 - 18	W 9	W 8; 9	275	885	395	2593	STD	10	TL	138 A6/131 A8
10.5/80 - 18	W 9	W 8; 9	275	885	395	2593	STD	14	TL	144 A6/138 A8
12.5/80 - 18	W 9	11	308	965	432	2827	STD	10	TL	145 A6/139 A8
12.5/80 - 18	W 9	11	308	965	432	2827	STD	12	TL	148 A6/142 A8
12.5/80 - 18	W 9	11	308	965	432	2827	STD	14	TL	152 A6/146 A8
12.5/80 - 18	W 9	11	308	965	432	2827	SPL	14	TL	152 A6/146 A8
12.5/80 - 18	W 9	11	308	965	432	2827	STD	16	TL	154 A6/150 A8
12.5/80 - 18	W 9	11	308	965	432	2827	SPL	16	TL	154 A6/150 A8
12.5/80 - 18	W 9	11	308	965	432	2827	STD	18	TL	156 A6/152 A8
13.0/65 - 18	11.0	-	336	890	398	2608	STD	14	TT	147 A6/141 A8
13.0/65 - 18	11.0	-	336	890	398	2608	STD	14	TL	147 A6/141 A8
13.0/65 - 18	11.0	-	336	890	398	2608	STD	16	TL	150 A6/144 A8
14.5/80 - 18	11.0	12; 13	362	1047	446	3068	STD	12	TT	155 A8

STD: Standard

SPL: Special version ②



AW 705



AW 705 has been developed for implement machinery and trailers in soil tillage and transport applications. It is ideal for modern farming both on and off the road. AW 705 is available also in a "special" version, which offers improved durability.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
16"										
14.0/65 - 16	11.0	-	353	870	388	2549	STD	10	TT	140 A6/ 136 A8
14.0/65 - 16	11.0	-	353	870	388	2549	STD	10	TL	140 A6/ 136 A8
14.0/65 - 16	11.0	-	353	870	388	2549	STD	14	TT	148 A6/145 A8
14.0/65 - 16	11.0	-	353	870	388	2549	STD	14	TL	148 A6/145 A8
17"										
15.0/55 - 17	13.00	13; W 13	391	850	377	2490	STD	10	TL	141 A6/134 A8
15.0/55 - 17	13.00	13; W 13	391	850	377	2490	STD	12	TL	144 A6/138 A8
15.0/55 - 17	13.00	13; W 13	391	850	377	2490	STD	14	TL	147 A6/141 A8
15.0/55 - 17	13.00	13; W 13	391	850	377	2490	STD	18	TL	152 A6/149 A8
18"										
15.0/70 - 18	13.00	13; W 13	391	990	442	2901	STD	12	TL	151 A6/145 A8
15.0/70 - 18	13.00	13; W 13	391	990	442	2901	STD	14	TL	154 A6/148 A8
15.0/70 - 18	13.00	13; W 13	391	990	442	2901	STD	16	TL	157 A6/151 A8
20"										
16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	12	TT	157 A6/151 A8
16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	12	TL	157 A6/151 A8
16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	14	TT	160 A6/156 A8
16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	14	TL	160 A6/156 A8
16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	SPL	14	TL	160 A6/156 A8
16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	16	TL	162 A6/159 A8
22.5"										
400/55 - 22.5	AG 11.75	12.25; AG 13.00	405	1016	443	3072	STD	18	TL	154 A8/150 B

SPL: Special version ^①
STD: Standard

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

IMPLEMENT TIRES



AW 708



AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and hay harvesters/balers. It is ideal for modern farming both on and off the road.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15.5"										
400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	10	TL	143 A6/136 A8
400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	14	TT	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	14	TL	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	18	TL	155 A6/149 A8
17"										
19.0/45 - 17	16.00	-	491	866	380	2536	STD	10	TL	144 A6/138 A8
19.0/45 - 17	16.00	-	491	866	380	2536	STD	14	TL	150 A6/144 A8
19.0/45 - 17	16.00	-	491	866	380	2536	STD	18	TL	160 A6/156 A8
500/50 - 17	16.00	-	500	945	416	2750	STD	10	TL	149 A6/145 A8
500/50 - 17	16.00	-	500	945	416	2750	STD	14	TL	155 A6/152 A8
500/50 - 17	16.00	-	500	945	416	2750	STD	16	TL	158 A6/155 A8
500/50 - 17	16.00	-	500	945	416	2750	STD	18	TL	160 A6/157 A8
500/65 - 17	16.0	-	520	1070	462	3135	STD	18	TL	167 A6/161 A8

STD: Standard





AW 909



AW 909 has been developed for soil tillage and transport applications with implement machinery and trailers. It is ideal for modern farming both on and off the road. Besides, it provides a high level of handling comfort.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12"										
10.0/80 - 12	9.00	7.0	264	710	313	2080	STD	8	TL	122 A6/116 A8
10.0/80 - 12	9.00	7.0	264	710	313	2080	STD	10	TL	126 A6/121 A8
15.3"										
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	10	TL	128 A6/123 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	12	TL	132 A6/128 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	14	TL	136 A6/130 A8
10.0/75 - 15.3	9.00	-	274	760	343	2227	STD	18	TL	142 A6/138 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	10	TL	137 A6/131 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	12	TL	141 A6/135 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	14	TL	145 A6/139 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	16	TT	147 A6/141 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	16	TL	147 A6/141 A8
11.5/80 - 15.3	9.00	-	297	844	370	2473	STD	18	TL	149 A6/145 A8
12.5/80 - 15.3	9.00	-	312	885	387	2593	STD	14	TL	147 A6/142 A8
17"										
15.0/55 - 17	13.00	13	391	850	377	2490	STD	10	TL	141 A6/134 A8
15.0/55 - 17	13.00	13	391	850	377	2490	STD	12	TL	144 A6/138 A8
15.0/55 - 17	13.00	13	391	850	377	2490	STD	14	TL	147 A6/141 A8

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



AW 09



FREE ROLLING
APPLICATION



CUT RESISTANT



HIGH PUNCTURE
RESISTANCE



DURABILITY

AW 09 has been developed for soil tillage and transport applications with implement machinery and trailers. It is ideal for modern farming both on and off the road. AW 09 is the right tire to be used in all operating conditions which require excellent handling features.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.									
15.3"											
260/70 - 15.3	9.00	-	268	753	335	2206	STD	-	TL	110 A8	122 A8
260/70 - 15.3	9.00	-	268	753	335	2206	STD	-	TL	114 A8	126 A8
260/70 - 15.3	9.00	-	268	753	335	2206	STD	-	TL	119 A8	131 A8
300/80 - 15.3	9.00	-	295	860	376	2520	STD	-	TL	120 A8	132 A8
300/80 - 15.3	9.00	-	295	860	376	2520	STD	-	TL	126 A8	138 A8
300/80 - 15.3	9.00	-	295	860	376	2520	STD	-	TL	129 A8	141 A8
320/80 - 15.3	9.00	-	309	901	392	2640	STD	-	TL	133 A8	145 A8
15.5"											
400/60 - 15.5	AG 13.00	-	404	874	382	2561	STD	-	TL	132 A8	145 A8
17"											
380/55 - 17	13.00	-	390	850	377	2491	STD	-	TL	125 A8	138 A8
380/55 - 17	13.00	-	390	850	377	2491	STD	-	TL	128 A8	141 A8

STD: Standard





RIB IMPLEMENT



RIB IMPLEMENT has been engineered for trailers and implement machinery in transport and soil tillage applications. It is ideal for modern farming and shows top performance both on and off the road. RIB IMPLEMENT is the right choice for all operating conditions which require a high level of handling as well as reduced soil compaction to preserve the crops.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 10.0/80 - 12	9.00	7.0	264	746	329	2186	STD	6	TL	117 A6/110 A8
17" 49 - 17	13.0	14.0	264	746	329	2186	STD	20	TL	-

STD: Standard



RIB 713 (I-1)



RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The steel-belted structure provides excellent puncture resistance and hence increased protection against stub penetration and relative damages, even if running into strong stubble. In addition, "D" speed rating (65 km/h – 40 mph) allows for fast road transfers. RIB 713 is BKT's contribution to maximize both the productivity and efficiency of your farming business.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
		Rec.	Alt.						
15" IF 280/70 R 15	128 D	8	-	279	779	347	2356	360	STD

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



RIB 774 (A)



RIB 774 (A) is a low section implement tire offering high load capacity with minimum soil compaction. It is ideal for modern farming and suitable for on- and off-the-road applications.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
17" 15.0/55 - 17	13.00	13	391	850	377	2490	STD	10	TL	141 A6/134 A8
15.0/55 - 17	13.00	13	391	850	377	2490	STD	14	TL	147 A6/141 A8

STD: Standard



RIB 774 (B)



RIB 774 (B) is a low section implement tire. It is ideal for modern farming and suitable for on- and off-the-road applications.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
14.5" 200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	10	TT	113 A6/109 A8
200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	10	TL	113 A6/109 A8
200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	14	TT	115 A6/111 A8
200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	14	TL	115 A6/111 A8
250/65 - 14.5	AG 8.00	6.75	255	675	303	1978	STD	12	TL	125 A6/123 A8
250/65 - 14.5	AG 8.00	6.75	255	675	303	1978	STD	14	TL	130 A6/126 A8
16" 10.5/65 - 16	W 9	W 8 L	265	745	339	2183	STD	14	TT	137 A6/130 A8
10.5/65 - 16	W 9	W 8 L	265	745	339	2183	IND	14	TT	137 A6/130 A8
18" 12.0 - 18 (340/70 - 18)	11.0	-	342	902	414	2688	STD	16	TL	156 A6/153 A8

STD: Standard
IND: Industrial



RIB 774 (C)



RIB 774 (C) is a low section and narrow width implement tire. It is ideal for modern farming and suitable for on- and off-the-road applications.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
17"										
19.0/45 - 17	16.00	-	455	845	387	2518	STD	10	TT	144 A6/138 A8
17.5"										
215/75 - 17.5	6.75	-	220	775	360	2310	STD	12	TL	138 A8/134 A6
215/75 - 17.5	6.75	-	220	775	360	2310	STD	16	TL	149 A6/145 A8
225/75 - 17.5	6.75	-	220	775	360	2310	STD	12	TL	142 A6/139 A8
225/75 - 17.5	6.75	-	220	775	360	2310	STD	16	TL	148 A6/145 A8

STD: Standard



Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



RIB 775



RIB 775 is a low-section cross-ply tire for transport and soil tillage applications with trailers and implement machinery. It offers excellent handling as well as reduced soil compaction.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 300/65 - 12	9.0	-	305	685	304	2007	STD	8	TL	122 A6/119 A8

STD: Standard



RIB 900



RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and hay harvesters/balers. It offers excellent handling as well as reduced soil compaction.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15.5" 400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	10	TL	143 A6/136 A8
400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	14	TL	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	16	TL	153 A6/147 A8

STD: Standard



RIB MASTER

RIB MASTER is suitable for transport and soil tillage operations with trailers and implement machinery. This tire is ideal in all operating conditions that require excellent handling.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
17.5" 215/75 - 17.5	6.75	-	220	775	360	2310	STD	16	TL	143 A6/140 A8

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



FLOTATION RIB IMPLEMENT



FLOTATION RIB IMPLEMENT is a rib pattern tire for trailers in transport applications. It features high flotation capability and ensures significant fuel savings to boost the productivity of your business.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15" 31 X 13.50 - 15	10 LB	-	360	780	359	2129	STD	12	TL	-

STD: Standard



MULTI RIB



MULTI RIB is an agro-industrial tire for soil tillage and transport applications with 2WD tractors, trailers, and implement machinery. It offers excellent handling throughout its long product life-cycle.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
16" 11.00 - 16	W10 L	W 8; W 8 L	315	930	-	-	STD	12	TL	-

STD: Standard



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 6.5/80 - 12	5 J	5 JA	163	588	273	1743	STD	4	TT	90 A6/87 A8
6.5/80 - 12	5 J	5 JA	163	588	273	1743	STD	4	TL	90 A6/87 A8
6.5/80 - 12	5 J	5 JA	163	588	273	1743	STD	6	TT	99 A6/96 A8
6.5/80 - 12	5 J	5 JA	163	588	273	1743	STD	6	TL	99 A6/96 A8
7.00 - 12	4.5	-	187	683	300	2001	STD	4	TT	94 A6/88 A8
7.00 - 12	4.5	-	187	683	300	2001	STD	4	TL	94 A6/88 A8
7.00 - 12	4.5	-	187	683	300	2001	STD	6	TL	101 A6/95 A8
7.00 - 12	4.5	-	187	683	300	2001	SPL	8	TL	107 A6/ 100 A8
11.0/65 - 12	9.00	-	273	700	321	2072	STD	8	TT	120 A6/ 116 A8
11.0/65 - 12	9.00	-	273	700	321	2072	STD	8	TL	120 A6/ 116 A8

SPL: Special version ③
STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

IMPLEMENT TIRES



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15"										
5.00 - 15	3.50 D	3.00 D; 4.00 E; 4 J	140	657	308	1957	STD	4	TT	86 A6/82 A8
5.00 - 15	3.50 D	3.00 D; 4.00 E; 4 J	140	657	308	1957	STD	6	TT	94 A6/90 A8
7.5L - 15	6 LB	5 K; 5 J; 5 K	210	765	354	2280	STD	6	TT	116 A6/112 A8
7.5L - 15	6 LB	5 K; 5½ J; 5½ K	210	765	354	2280	STD	8	TT	119 A6/115 A8
7.5L - 15	6 LB	5 K; 5½ J; 5½ K	210	765	354	2280	STD	8	TL	119 A6/115 A8
7.5L - 15	6 LB	5 K; 5½ J; 5½ K	210	765	354	2280	HD	8	TT	119 A6/115 A8
15.3"										
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	8	TT	124 A6/119 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	8	TL	124 A6/119 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	IND	8	TL	124 A6/119 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	10	TL	128 A6/123 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	14	TL	136 A6/130 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	18	TT	142 A6/138 A8
10.0/75 - 15.3	9.00	-	264	780	345	2285	STD	18	TL	142 A6/138 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	8	TT	133 A6/126 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	8	TL	133 A6/126 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	10	TL	137 A6/131 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	12	TT	141 A6/135 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	12	TL	141 A6/135 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	14	TT	145 A6/139 A8
11.5/80 - 15.3	9.00	-	290	867	380	2540	STD	14	TL	145 A6/139 A8
27 X 10 - 15.3	9.00	-	260	695	317	2071	STD	8	TT	114 A6/110 A8
27 X 10 - 15.3	9.00	-	260	695	317	2071	STD	8	TL	114 A6/110 A8

HD: Heavy Duty Version ①
IND: Industrial ②
STD: Standard



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
16"										
6.00 - 16	4.00 E	4.50 E; 4½ K	164	735	343	2190	STD	6	TT	101 A6/98 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	STD	6	TT	111 A6/ 107 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	STD	8	TT	119 A6/115 A8
7.50 - 16	5.50 F	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F	209	803	372	2393	STD	8	TL	119 A6/115 A8
17"										
15.0/55 - 17	13.00	13	380	890	395	2608	STD	10	TL	141 A6/134 A8
15.0/55 - 17	13.00	13	380	890	395	2608	STD	14	TL	147 A6/141 A8
19.0/45 - 17	16.00	-	465	865	389	2578	STD	14	TL	150 A6/146 A8
420/55 - 17	13.00	-	430	910	407	2712	STD	14	TL	-
420/55 - 17	13.00	-	430	910	407	2712	STD	16	TL	-
18"										
7.50 - 18	5.50 F	4.50 E; 6.00 F; 5.00 F	209	854	407	2649	STD	6	TT	113 A6/109 A8
7.50 - 18	5.50 F	4.50 E; 6.00 F; 5.00 F	209	854	407	2649	STD	8	TT	120 A6/ 117 A8
10.5/80 - 18	W 9	9; W 8	274	907	405	2657	STD	10	TL	138 A6/131 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	STD	12	TL	148 A6/142 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	STD	16	TL	154 A6/150 A8
12.5/80 - 18	W 9	9; 11	308	987	438	2892	STD	18	TL	156 A6/150 A8

STD: Standard

Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

IMPLEMENT TIRES



AS 504



AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS	
	Rec.	Alt.									
											
20"	7.50 - 20	5.50 F	4.50 E; 6.00 F; 5.00 F	209	904	422	2695	STD	8	TT	122 A6/119 A8
	16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	10	TL	153 A6/147 A8
	16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	12	TL	157 A6/151 A8
	16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	14	TL	160 A6/1564 A8
	16.0/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	STD	16	TL	162 A6/156 A8
	400/70 - 20	13	12 SDC; 14; 13 SDC	408	1097	487	3214	IND	-	TL	149 A8
24"	15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	10	TL	160 A6/154 A8
	15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	12	TL	163 A6/157 A8
	15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	14	TL	166 A6/160 A8
	15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	SPL	14	TL	166 A6/160 A8
	15.5/80 - 24	W 12	W 13; W 14 L	384	1262	566	3655	STD	16	TL	169 A6/163 A8
	16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	10	TL	165 A6/161 A8
	16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	12	TL	169 A6/165 A8
	16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	16	TT	174 A6/170 A8
	16.5/85 - 24	W 13	W 14 L; W 15 L	415	1325	591	3837	STD	16	TL	174 A6/170 A8
	400/80 - 24	W 13	W 12; W 14 L	394	1262	566	3655	IND	-	TL	156 A8
	400/80 - 24	W 13	W 12; W 14 L	394	1262	566	3655	IND	-	TL	162 A8

IND: Industrial ②

SPL: Special version ③

STD: Standard



AS 505



AS 505 is best suited for soil tillage operations with small tractors and implement machinery. It features excellent self-cleaning properties and increased traction on the ground, especially on muddy soil.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15" 6.5/80 - 15	5.0	4½ K; 5 K; 5 J	163	663	310	1976	STD	6	TL	104 A6/101 A8
6.5/80 - 15	5.0	4½ K; 5 K; 5 J	163	663	310	1976	STD	8	TL	110 A6/ 106 A8

STD: Standard



AS 507



AS 507 is a field-oriented tire suitable for soil tillage with implement machinery. It features excellent self-cleaning properties and increased traction on the ground. The AS 507 "special" version offers even higher cut and chip resistance to face the most difficult operating conditions.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS Free Rolling	LI/SS Drive Wheel
	Rec.	Alt.									
15" 185/65 - 15	5.5	-	185	640	301	1894	STD	4	TL	73 A8	85 A8

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

IMPLEMENT TIRES



TR 882



TRACTION



HIGH LOAD
CAPACITY AT
STANDARD PRESSURE



AGRO-INDUSTRIAL
USE



CUT & CHIP
RESISTANCE



HEAVY DUTY SERVICE



HIGH PUNCTURE
RESISTANCE

TR 882 is a very versatile tire suitable for several applications and vehicles. Designed to fit implement machinery and hay harvesters/balers, its usage is not only limited to soil tillage and hay harvesting operations. BKT has developed a specific TR 882 version to use the tire in forestry applications with trailers. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15.5" 400/60 - 15.5	AG 13.00	-	400	875	380	2564	STD	8	TL	138 A6/132 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	STD	14	TL	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	AB	14	TL	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	HD	14	TL	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	SPL	14	TL	149 A6/143 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	STD	18	TL	155 A6/149 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	HD	18	TL	155 A6/149 A8
400/60 - 15.5	AG 13.00	-	400	875	380	2564	SPL	18	TL	155 A6/149 A8

AB: Aramid belted version

HD: Heavy Duty version ①

SPL: Special version ②

STD: Standard





SL 441



SL 441 is a free rolling tire developed for soil tillage operations with trailers and implement machinery. SL 441 has been engineered to provide best handling to drivers.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
14.5" 200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	10	TT	113 A6/109 A8
200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	14	TT	115 A6/111 A8
200/60 - 14.5	6.75	4.50 E; 5.50 F	210	610	278	1785	STD	14	TL	115 A6/111 A8

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
 Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
 20831 Seregno (MB), Italy
 Tel: (+39) 0362 33 03 28
 (+39) 0362 32 51 07
 Fax: (+39) 0362 23 24 72

BKT USA Inc. (AG Division)

2660 West Market St. Suite 100
 Fairlawn (Akron) OH 44333, USA
 Tel: (+1) 330 836 1090
 Fax: (+1) 330 836 1091
 Toll Free: (+1) 888 660 0662

BKT Tires, Inc. (OTR Division)

12 Cadillac Drive, Suite 240
 Brentwood, Tennessee 37027, USA
 Toll Free: (+1) 844 258 8473
 Fax: (+1) 888 290 1804

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
 Toronto, Ontario M5J 1R7, Canada
 Tel: AG/IND (+1) 905 641 5636
 OTR (+1) 780 888 5667
 Fax: (+1) 416 229 1711