



LAWN & GARDEN TIRES



LAWN & GARDEN TIRES



AT 316



AT 316 is suitable for compact utility tractors in municipality and maintenance applications. The special tread design provides excellent traction without compromising field protection - an essential feature for this kind of application. AT 316 is also available as "aramid-belted" version to provide increased puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 24 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	-	315	610	271	1769	STD	4	TL	-
24 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	-	315	610	271	1769	AB	6	TL	-

STD: Standard

AB: Aramid Belted Version ①



TR 360



TR 360 is suitable for implement machinery in hay harvesting and lawn and garden applications. The particular tread design along with the casing structure provides excellent stability in all field conditions and ensures a long tire life-cycle.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8" 18 X 7 - 8	5.5	-	180	460	202	1334	STD	6	TL	-

STD: Standard



LG SMOOTH



LG SMOOTH is a lawn and garden tire suitable for mowers. While the tire is gentle on the ground, the enhanced design ensures increased durability and eases handling. LG SMOOTH is available in an "aramid-belted" version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
10" 18 X 10.50 - 10	8.5 I - 55; I - 70; I - 90	8½ JA	254	460	207	1334	STD	2	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55; I - 70; I - 90	245	500	223	1450	STD	2	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55; I - 70; I - 90	245	500	223	1450	STD	4	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55; I - 70; I - 90	245	500	223	1450	STD	6	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55; I - 70; I - 90	245	500	223	1450	AB	6	TL	-

AB: Aramid Belted Version

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

LAWN & GARDEN TIRES



LG 306



FIELD
PROTECTION



DURABILITY



HANDLING



HIGH PUNCTURE
RESISTANCE ①

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for transport operations with airport cruise cars and small tractors in municipality/maintenance applications. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time.

LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS	
	Rec.	Alt.									
											
5"	11 X 4.00 - 5	3.00 A	-	104	272	120	789	STD	4	TL	-
6"	13 X 5.00 - 6	3.50 A	-	127	325	144	943	STD	4	TL	-
	13 X 5.00 - 6	3.50 A	-	127	325	144	943	STD	6	TL	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	4	TL	-
	15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	6	TL	-
8"	16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	4	TL	-
	16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	6	TL	-
	16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	AB	6	TL	-
	16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	8	TL	-
	18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	215	450	198	1305	STD	4	TL	-
	18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	215	450	198	1305	STD	6	TL	-
	18 X 9.50 - 8	7.00 I - 55; I - 70; I - 90	-	230	470	206	1363	STD	4	TL	-

STD: Standard

AB: Aramid belted version ①





LG 306



LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for transport operations with airport cruise cars and small tractors in municipality/maintenance applications. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time.

LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
										
18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	215	450	198	1305	AB	6	TL	-
18 X 9.50 - 8	7.00 I - 55; I - 70; I - 90	-	230	470	206	1363	STD	6	TL	-
18 X 9.50 - 8	7.00 I - 55; I - 70; I - 90	-	230	470	206	1363	AB	6	TL	-
20 X 10.00 - 8	8.00 I - 55	7.00 I - 55; I - 70; I - 90	254	508	221	1473	STD	4	TL	-
20 X 10.00 - 8	8.00 I - 55	7.00 I - 55; I - 70; I - 90	254	508	221	1473	STD	6	TL	-
20 X 10.00 - 8	8.00 I - 55	7.00 I - 55; I - 70; I - 90	254	508	221	1473	AB	6	TL	-
										
18 X 8.50 - 10	7.00 I - 55; I - 70; I - 90	-	210	460	209	1340	STD	4	TL	-
20 X 8.00 - 10	6.00 I - 55; I - 70; I - 90	6 JA	205	500	223	1450	STD	4	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55	250	508	226	1473	STD	4	TL	-
20 X 8.00 - 10	6.00 I - 55; I - 70; I - 90	6 JA	205	500	223	1450	STD	6	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55	250	508	226	1473	STD	6	TL	-
20 X 10.00 - 10	8.00 I - 55	7.00 I - 55	250	508	226	1473	AB	6	TL	-

STD: Standard

AB: Aramid belted version ①

Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index

LAWN & GARDEN TIRES



LG 306



FIELD
PROTECTION



DURABILITY



HANDLING



HIGH PUNCTURE
RESISTANCE ^①

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for transport operations with airport cruise cars and small tractors in municipality/maintenance applications. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time.

LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 23 X 8.50 - 12	7.00 I - 55; I - 70; I - 90	7 JA	210	575	258	1668	STD	4	TL	-
23 X 8.50 - 12	7.00 I - 55; I - 70; I - 90	7 JA	210	575	258	1668	STD	6	TL	-
23 X 8.50 - 12	7.00 I - 55; I - 70; I - 90	7 JA	210	575	258	1668	AB	6	TL	-
23 X 8.50 - 12	7.00 I - 55; I - 70; I - 90	7 JA	210	575	258	1668	STD	8	TL	-
23 X 8.50 - 12	7.00 I - 55; I - 70; I - 90	7 JA	210	575	258	1668	STD	12	TL	-
23 X 10.50 - 12	8.5 I - 55	7.00 I - 55; I - 70; I - 90	260	585	262	1697	STD	4	TL	-
23 X 10.50 - 12	8.5 I - 55	7.00 I - 55; I - 70; I - 90	260	585	262	1697	STD	6	TL	-
23 X 10.50 - 12	8.5 I - 55	7.00 I - 55; I - 70; I - 90	260	585	262	1697	AB	6	TL	-
23 X 10.50 - 12	8.5 I - 55	7.00 I - 55; I - 70; I - 90	260	585	262	1697	STD	8	TL	-
23 X 10.50 - 12	8.5 I - 55	7.00 I - 55; I - 70; I - 90	260	585	262	1697	STD	12	TL	-
24 X 12.00 - 12	9.5 AT	9.0 AT; 8.5 AT; 8.0 AT	298	610	276	1774	STD	4	TL	-
26 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	10½ JA; 8½ JA	310	640	283	1856	STD	4	TL	-
26 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	10½ JA; 8½ JA	310	640	283	1856	AB	6	TL	-
26 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	10½ JA; 8½ JA	310	640	283	1856	STD	8	TL	-
26 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	10½ JA; 8½ JA	310	640	283	1856	AB	8	TL	-
26 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	10½ JA; 8½ JA	310	640	283	1856	STD	12	TL	-
26 X 12.00 - 12	10.50 I - 55; I - 70; I - 90	10½ JA; 8½ JA	310	640	283	1856	STD	14	TL	-

STD: Standard

AB: Aramid belted version ^①



LG 306



FIELD
PROTECTION



DURABILITY



HANDLING



HIGH PUNCTURE
RESISTANCE ^①

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for transport operations with airport cruise cars and small tractors in municipality/maintenance applications. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time.

LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec. 	Alt.								
14"										
24 X 8.50 - 14	7 JA	-	210	610	280	1769	STD	4	TL	-
25 X 8.50 - 14	7.00 I - 55; I - 70; I - 90	-	220	638	333	1914	STD	6	TL	-
15"										
27 X 8.50 - 15	7.00 JA	-	216	680	308	1970	STD	4	TL	-
27 X 10.50 - 15	8.00 LB	-	272	705	318	2042	STD	4	TL	-
27 X 10.50 - 15	8.00 LB	-	272	705	318	2042	STD	12	TL	-
31 X 15.5 - 15	13 LB	-	391	792	350	2313	STD	4	TL	-
16"										
13.6 - 16	W 12	W 11	388	975	414	2847	STD	4	TL	-
16.5"										
33 X 15.50 - 16.5	12.00	-	396	840	374	2453	STD	10	TL	-
20"										
38 X 14.00 - 20	W 11	W 11 H	375	980	435	2894	STD	4	TL	-
44 X 18.00 - 20	W 14 L	W 14 LH	475	1180	543	3496	STD	4	TL	-

STD: Standard

AB: Aramid belted version ^①

Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

LAWN & GARDEN TIRES



LG 307



LG 307 is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages, easing handling at the same time.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8"										
20 X 10.00 - 8	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	255	495	215	1435	STD	4	TL	-
20 X 10.00 - 8	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	255	495	215	1435	STD	6	TL	-
10"										
20 X 12.00 - 10	8.5 I - 55; I - 70; I - 90	-	285	500	221	1435	STD	4	TL	-

STD: Standard





LG 408



LG 408 is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages. LG 408 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
24 X 13.00 - 12	10.5 I - 55; I - 70; I - 90	-	320	605	269	1755	STD	4	TL	-
24 X 13.00 - 12	10.5 I - 55; I - 70; I - 90	-	320	605	269	1755	STD	6	TL	-
24 X 13.00 - 12	10.5 I - 55; I - 70; I - 90	-	320	605	269	1755	AB	6	TL	-
26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	4	TL	-
26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	6	TL	-
26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	AB	6	TL	-

STD: Standard

AB: Aramid belted version ①

Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

LAWN & GARDEN TIRES



LG RIB



LG RIB is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages and ensures a long product life. LG RIB is available in an “aramid-belted” version for users who need strengthened puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
										
6"										
13 X 5.00 - 6	3.50 A	-	127	325	144	943	STD	4	TL	-
13 X 5.00 - 6	3.50 A	-	127	325	144	943	AB	6	TL	-
15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	4	TL	-
15 X 6.00 - 6	4.50 A	-	152	365	159	1059	STD	6	TL	-
15 X 6.00 - 6	4.50 A	-	152	365	159	1059	AB	6	TL	-
8"										
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	4	TT	-
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	4	TL	-
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	6	TL	-
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	AB	6	TL	-
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	8	TL	-
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	170	408	182	1183	STD	10	TL	-
10"										
20 X 10.00 - 10	8.00 I - 55; I - 70; I - 90	7.00 I - 55; I - 70; I - 90	236	498	222	1444	STD	4	TL	-

STD: Standard

AB: Aramid belted version ①



TRAC MASTER



TRAC MASTER is a soil tillage and lawn and garden tire, suitable for small tractors, implement machinery, compact loaders, and mowers. It has been designed to improve traction, while the wider footprint ensures great stability.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 300/60 - 12	10.5	9.5	306	645	285	1885	STD	8	TL	-
15" 31 X 15.50 - 15	13 LB	-	405	810	357	2365	STD	6	TL	-
31 X 15.50 - 15	13 LB	-	405	810	357	2365	STD	8	TL	-
33 X 15.50 - 15	13 LB	-	404	865	378	2526	STD	6	TL	-
33 X 15.50 - 15	13 LB	-	404	865	378	2526	STD	8	TL	-

STD: Standard



TR 313



TR 313 is suitable for soil tillage and lawn and garden operations with implement machinery, trenchers and orchard harvesters. It is an ideal tire for muddy grounds. The large contact area provides an excellent grip. The TR 313 tire has been engineered to ensure a high level of stability also in critical operating conditions.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
15" 31 X 15.50 - 15	13 LB	-	370	770	342	2233	STD	8	TL	-

STD: Standard

Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5%
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

LAWN & GARDEN TIRES



TR 315



TRACTION



SUITABLE FOR
MUDDY GROUND



STABILITY



SPECIAL
COMPOUND ①

TR 315 is suitable for muddy grounds in soil tillage and lawn and garden operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip and outstanding stability in any condition.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS	
	Rec.	Alt.									
											
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	155	408	182	1183	STD	4	TL	-	
16 X 6.50 - 8	5.375 I - 55; I - 70; I - 90	-	155	408	182	1183	STD	6	TL	-	
											
23 X 8.50 - 12	7 JA; 7.00 I - 55; I - 70; I - 90	-	205	575	258	1668	STD	4	TL	-	
23 X 8.50 - 12	7 JA; 7.00 I - 55; I - 70; I - 90	-	205	575	258	1668	STD	6	TL	-	
23 X 10.50 - 12	8½ JA	7 JA	255	590	260	1682	STD	4	TL	-	
23 X 10.50 - 12	8½ JA	7 JA	255	590	260	1682	STD	6	TL	-	
23 X 10.50 - 12	8½ JA	7 JA	255	590	260	1682	STD	8	TL	-	
23 X 10.50 - 12	8½ JA	7 JA	255	590	260	1682	STD	10	TL	-	
26 X 12.00 - 12	10½ JA	8½ JA; 9½ JA	308	655	289	1905	STD	4	TL	-	
26 X 12.00 - 12	10½ JA	8½ JA; 9½ JA	308	655	289	1905	STD	8	TL	-	
26 X 12.00 - 12	10½ JA	8½ JA; 9½ JA	308	655	289	1905	STD	10	TL	-	
26 X 12.00 - 12	10½ JA	8½ JA; 9½ JA	308	655	289	1905	SPL	10	TL	-	
26 X 12.00 - 12	10½ JA	8½ JA; 9½ JA	308	655	289	1905	STD	12	TL	-	
											
31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	8	TL	-	
31 X 15.50 - 15	13 LB	-	390	800	354	2320	STD	10	TL	-	
31 X 15.50 - 15	10 LB	-	390	800	354	2320	STD	12	TL	-	

STD: Standard

SPL: Special version ①



TR 317



TRACTION



SUITABLE FOR
MUDDY GROUND



STABILITY

TR 317 is suitable for soil tillage operations on muddy grounds with implement machinery and trenchers. The TR 317 tire has a large contact area which provides excellent grip and outstanding stability in any condition.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8" 18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	215	450	198	1305	STD	4	TL	-

STD: Standard



TR 319



TRACTION



SUITABLE FOR
MUDDY GROUND



STABILITY

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden as well as soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet and dry surfaces.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
12" 26 X 12.00 - 12	10.50 AT	8.0 AT; 8.5 AT; 9.0 AT	318	640	-	-	STD	8	TL	116 A3

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

LAWN & GARDEN TIRES



GF 304



DURABILITY



COMFORT



FIELD
PROTECTION



HIGH PUNCTURE
RESISTANCE

①

GF 304 is suitable for soil tillage applications with implement machinery and trenchers. No matter which soil tillage operation you are performing on your field, GF 304 will ensure best comfort and ground protection. GF 304 is also available as "aramid-belted" version to provide increased puncture resistance.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
8"										
18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	216	460	202	1334	STD	4	TL	-
18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	216	460	202	1334	AB	4	TL	-
18 X 8.50 - 8	7.00 I - 55; I - 70; I - 90	-	216	460	202	1334	STD	6	TL	-

STD: Standard

AB: Aramid belted version ①



GF 305 CLASSIC



DURABILITY



COMFORT



FIELD
PROTECTION

GF 305 CLASSIC is a special tire mainly designed for golf carts, but it is also suitable for some hay harvesting operations with implement machinery. This tire is naturally gentle on the ground and protects the field from damages. GF 305 CLASSIC is a really comfortable tire which makes riding a pleasure.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
10"										
205/50 - 10	7.00 I - 55	6.00 I - 55; I - 70; I - 90	215	470	211	1363	STD	4	TL	-

STD: Standard





GF 305 FARM TRAILER

GF 305 FARM TRAILER has been designed for trailers in transport operations. This tire is particularly suitable for heavy-duty service and provides outstanding stability in any condition.

SIZE	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	TYPE	LI/SS
	Rec.	Alt.								
10" 205/65 - 10 (20.5 x 8.00 - 10)	6.00	-	212	520	223	1508	STD	10	TL	-

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

2660 West Market St. Suite 100
Fairlawn (Akron) OH 44333, USA
Tel: (+1) 330 836 1090
Fax: (+1) 330 836 1091
Toll Free: (+1) 888 660 0662

BKT Tires, Inc.

12 Cadillac Drive, Suite 240
Brentwood, Tennessee 37027, USA
Toll Free: (+1) 844 258 8473
Fax: (+1) 330 836 1091

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 905 641 5636
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711