



**ROW CROP
TIRES**

ROW CROP TIRES



AGRIMAX RT 855 (R-1W)



AGRIMAX RT 855 is a tire featuring excellent traction and comfort properties. It has been designed mainly for soil tillage and field and road transport, but some sizes are also suitable for row crop, spraying and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
		Rec.	Alt.						
32" 320/85 R 32 (12.4 R 32)	126 A8/B	W 11	W 9; W 10	329	1357	621	4081	650	STD
36" 320/85 R 36 (12.4 R 36)	128 A8/B	W 11	W 9; W 10	329	1458	672	4404	700	STD
340/85 R 36 (13.6 R 36)	132 A8/B	W 12	W 11	353	1492	689	4507	725	STD
38" 320/85 R 38 (12.4 R 38)	143 A8/B	W 10	W 9; W 11; DW 11	319	1509	700	4580	725	STD
340/85 R 38 (13.6 R 38)	133 A8/B	W 12	W 11	353	1543	712	4613	750	STD
380/85 R 38 (14.9 R 38)	139 A8/B	W 12	W 11; W 13	380	1611	736	4841	775	STD
420/85 R 38 (16.9 R 38)	144 A8/B	W 15 L	W 13; W 14 L	438	1679	763	4992	800	STD
460/85 R 38 (18.4 R 38)	149 A8/B	W 16 L	W 14 L; W 15 L	475	1747	785	5161	825	STD
480/80 R 38 (18.4 R 38)	149 A8/B	W 16 L	W 14 L; W 15 L	475	1747	785	5161	825	STD
520/85 R 38 (20.8 R 38)	155 A8/B	DW 16 L	DW 18 L; DD 16 L	516	1849	813	5393	875	STD
520/85 R 38 (20.8 R 38)	170 A8/B	DW 16 L	DW 18 L; DD 16 L	516	1849	813	5393	875	STD

STD: Standard





AGRIMAX SPARGO (R-1)



AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and preserving the soil in the long term. The tire provides excellent self-cleaning features in addition to higher load capacity at standard pressure. AGRIMAX SPARGO ensures an outstanding traction along with strong stability both in the fields and during road transfers.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
		Rec.	Alt.						
38" VF 380/85 R 38	161 D	W 13	W 12	380	1602	730	4830	775	STD
46" VF 380/90 R 46	173 D	DW 13 A	W 13 A; DW 12	390	1852	846	5611	875	STD

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

ROW CROP TIRES



AGRIMAX RT 945 (R-1W)



TRACTION



SELF-CLEANING



STABILITY



DURABILITY



FIELD PROTECTION

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. It is suitable for compact utility tractors in municipality and maintenance applications.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version	
		Rec.	Alt.							
										
42"	320/90 R 42 (12.4 R 42)	139 A8/B	W 10	W 9; W 11	319	1643	760	4944	800	STD
46"	320/90 R 46 (12.4 R 46)	146 A8/B	W 10	W 9; W 11	319	1744	810	5232	825	STD
	380/90 R 46 (14.9 R 46)	155 A8/B	W 12	W 11; W 13	380	1852	859	5596	875	STD
	380/90 R 46 (14.9 R 46)	159 A8/B	W 12	W 11; W 13	380	1852	859	5596	875	STD
50"	320/90 R 50 (12.4 R 50)	150 A8/B	W 10	W 9; W 11	319	1846	873	5618	875	STD
	380/90 R 50 (14.9 R 50)	151 A8/B	W 12	W 11; W 13	380	1954	913	5902	975	STD
54"	320/90 R 54 (12.4 R 54)	155 A8/B	W 10	W 9; W 11	319	1948	930	5987	925	STD
	380/90 R 54 (14.9 R 54)	158 A8/B	W 12	W 11; W 13	380	2056	962	6296	1025	STD

STD: Standard



AGRIMAX RT 955 (R-1)



TRACTION



SELF-CLEANING



STABILITY



DURABILITY



FIELD PROTECTION

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version	
		Rec.	Alt.							
 24"	210/90 R 24 (8.3 R 24)	107 A8/B	 W 7	 W 6	 214	 1010	 462	 3027	 500	STD
 28"	210/95 R 28 (8.3 R 28)	116 A8/B	W 7	W 6	214	1111	513	3333	550	STD
 32"	210/95 R 32 (8.3 R 32)	120 A8/B	W 7	W 6	214	1213	571	3703	575	STD
	230/95 R 32 (9.5 R 32)	128 A8/B	W 8	W 7	238	1251	585	3792	600	STD
	270/95 R 32 (11.2 R 32)	136 A8/B	W 9	W 8; W 10	275	1327	614	4044	625	STD
 36"	230/95 R 36 (9.5 R 36)	130 A8/B	W 8	W 7	238	1352	639	4112	650	STD
	270/95 R 36 (11.2 R 36)	139 A8/B	W 9	W 8; W 10	275	1428	665	4368	675	STD
 38"	270/95 R 38 (11.2 R 38)	140 A8/B	W 9	W 8; W 10	275	1479	697	4510	700	STD
 42"	230/95 R 42 (9.5 R 42)	133 A8/B	W 8	W 7	238	1506	714	4633	725	STD
	300/85 R 42 (11.2 R 42)	144 A8/B	W 9	W 10; W 11	295	1577	745	4850	750	STD

STD: Standard

Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$
 LI/SS = Load Index / Speed Symbol;
 S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference;
 SRI = Speed Radius Index

ROW CROP TIRES



AGRIMAX RT 955 (R-1)



AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

SIZE	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version	
		Rec.	Alt.							
										
44"	210/95 R 44 (8.3 R 44)	120 A8/B	W 7	W 6	214	1518	716	4554	725	STD
	230/95 R 44 (9.5 R 44)	134 A8/B	W 8	W 7	238	1556	739	4788	750	STD
	270/95 R 44 (11.2 R 44)	142 A8/B	W 9	W 8 ; W 10	275	1632	764	4983	775	STD
46"	270/95 R 46 (11.2 R 46)	143 A8/B	W 9	W 8 ; W 10	275	1683	786	5049	800	STD
	300/95 R 46 (12.4 R 46)	148 A8/B	W 9	W 10 ; W 1 ; DW 10 ; DW 11	295	1738	812	5318	825	STD
	300/95 R 46 (12.4 R 46)	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1738	812	5318	825	SPL
	340/85 R 46 (13.6 R 46)	150 A8/B	W 12	W 11	353	1746	811	5238	825	STD
48"	230/95 R 48 (9.5 R 48)	136 A8/B	W 8	W 7	238	1656	792	5085	800	STD
	270/95 R 48 (11.2 R 48)	144 A8/B	W 9	W 8 ; W 10	275	1733	820	5351	825	STD
	340/85 R 48 (13.6 R 48)	152 A8/B	W 12	W 11	353	1797	855	5572	875	STD
52"	300/95 R 52 (12.4 R 52)	151 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	295	1891	889	5822	925	STD
54"	270/95 R 54 (11.2 R 54)	146 A8/B	W 9	W 8 ; W 10	275	1885	878	5815	925	STD

STD: Standard
SPL: Special Version



Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5%
LI/SS = Load Index / Speed Symbol;
S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference;
SRI = Speed Radius Index



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
 Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
 20831 Seregno (MB), Italy
 Tel: (+39) 0362 33 03 28
 (+39) 0362 32 51 07
 Fax: (+39) 0362 23 24 72

BKT USA Inc. (AG Division)

2660 West Market St. Suite 100
 Fairlawn (Akron) OH 44333, USA
 Tel: (+1) 330 836 1090
 Fax: (+1) 330 836 1091
 Toll Free: (+1) 888 660 0662

BKT Tires, Inc. (OTR Division)

12 Cadillac Drive, Suite 240
 Brentwood, Tennessee 37027, USA
 Toll Free: (+1) 844 258 8473
 Fax: (+1) 888 290 1804

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
 Toronto, Ontario M5J 1R7, Canada
 Tel: AG/IND (+1) 905 641 5636
 OTR (+1) 780 888 5667
 Fax: (+1) 416 229 1711