

SMART Work AM09(+)

New all-position tire for mixed usage and enhanced on/off road performance



SMARTEC
HANKOOK TBR TECHNOLOGY



Polygonal blocks and zig-zag grooves

Ensure an excellent traction and braking performance both on site and on the road.



Extra wide tread pattern

The extra wide tread pattern with a closed shoulder design and integrated lugs supplies driving stability and a prolonged tread life.



Stone ejectors

Ensure grooves are kept clear at all times by using an additional rubber material to force unwanted debris out.



Sizes & Specifications (Pattern Code: AM09)

S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/Mile	SLR (Inch)	Max Speed	Weight (lbs)
					S	D	S	D								
* 3002557	11R24.5	16	T/L	8.25	120	120	7,160	6,610	43.7	11.3	8.8	24	472	20.2	65	131
3002698	12R22.5	16	T/L	9.00	120	120	7,390	6,780	42.9	12.0	9.2	24	483	20.0	65	137
3002703	11R22.5	16	T/L	8.25	120	120	6,610	6,005	41.7	11.3	8.8	24	494	19.5	68	125
* 3003590	255/70R22.5	16	T/L	7.50	120	120	5,510	5,070	36.7	9.9	8.3	19	559	16.9	75	95

Sizes & Specifications (Pattern Code: AM09+)

S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/Mile	SLR (Inch)	Max Speed	Weight (lbs)
					S	D	S	D								
3002789	315/80R22.5	20	T/L	9.00	130	130	10,000	9,090	42.6	12.5	10.4	22	485	19.6	65	151

* 4 Grooves: 315/80R22.5 AM09+ only

• Use inflation pressure specifications dependant on load.

• Tire construction and material specifications subject to change without notice or obligation.

* not 3PMSF

Recommended Vehicle Types & Position

○ Recommended position

