


SMART Work AM15(+)

All-Position radial tire for on and off-road conditions



Extra-wide tread blocks and deep grooves

Ensure ultra high mileage.



Open shoulder blocks with optimised tie-bars

Prevents irregular wear and provide excellent traction performance for off-road conditions.



Extra-wide grooves

Designed for excellent stone rejection and improved traction.



Sizes & Specifications (Pattern Code: AM15)

S-Code	Size	Ply Rating	Type	Measuring Rim	Tire Single		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	SLR (Inch)	Max Speed	Weight (lbs)
					Max. Air (PSI)	Max. Load (LBS)								
3001934	425/65R22.5	20	T/L	12.25	120	11,400	44.7	16.3	12.8	23	462	20.6	68	200
3002160	445/65R22.5	20	T/L	14.00	130	12,800	45.9	17.5	13.9	24	449	21.2	68	216

Sizes & Specifications (Pattern Code: AM15+)

S-Code	Size	Ply Rating	Type	Measuring Rim	Tire Single		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	SLR (Inch)	Max Speed	Weight (lbs)
					Max. Air (PSI)	Max. Load (LBS)								
3002813	385/65R22.5	18	T/L	11.75	120	9,370	42.5	14.9	12.0	23	485	19.6	75	166

- Use inflation pressure specifications dependant on load.
- Tire construction and material specifications subject to change without notice or obligation.

Recommended Vehicle Types & Position ○ Recommended position

