

SMART Flex TH31

All-season tire for variable road conditions



SMARTEC
HANKOOK TBR TECHNOLOGY



Main Zig-Zag Groove
Provides excellent traction and water drainage under various road conditions.



Groove Slant Design
Slanted groove design helps to prevent chunking.



Lateral Semi-Groove
Lateral groove helps improve initial traction performance.



Sizes & Specifications (Pattern Code: TH31)

S-Code	Size	Ply Rating	Type	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	SLR (Inch)	Max Speed	Weight (lbs)
					S	D	S	D								
3003528	255/70R22.5	16	T/L	7.50	120	120	5,510	5,070	36.6	9.8	8.0	17	562	17.1	75	91
3003744	215/75R17.5	16	T/L	6.00	123	123	4,805	4,540	30.5	8.4	7.3	15	672	14.2	65	64
3003745	235/75R17.5	18	T/L	6.75	127	127	6,005	5,675	31.5	9.4	8.6	16	653	14.5	65	69
3003746	245/70R17.5	18	T/L	7.50	127	127	6,005	5,675	31.5	9.8	8.6	16	650	14.5	65	69
3003747	750R16	14	T/L	6.00	110	110	3,415	3,000	31.8	8.9	5.9	15	648	14.9	65	56

• Use inflation pressure specifications dependant on load.
• Tire construction and material specifications subject to change without notice or obligation.
* 4 Grooves: 255/70R22.5 only, not 3PMSF

Recommended Vehicle Types & Position Recommended position

