



M+S



OH - 107


All position tyre for regional applications for trucks and buses



Five ribs & four straight and wide grooves for Excellent Traction and Precise Handling.



Solid Shoulder Ribs & Special Tread compound resists maneuvering scrub.



Linear grooves help in quicker drainage of water and kerfs on the inner ribs enhance traction.


OH - 107



Size	PR	Load Index	Speed Symbol	Tread Depth			
				mm			
10.00R20	16	147/143	L	15.0	D	A	70dB/A
10.00R20	18	149/145	J	15.0	D	A	70dB/A
11R22.5	16	148/145	M	15.0	C	A	70dB/A
12R22.5	16	152/148	M	16.0	C	A	70dB/A
255/70R22.5	16	140/137	L	13.5	C	A	70dB/A
275/70R22.5	16	148/145	M	15.0	C	A	70dB/A
295/60R22.5*	16	150/147	K	13.0	C	A	70dB/A
295/80R22.5	16	152/148	M	15.0	C	A	70dB/A
295/80R22.5	18	154/150	M	15.0	C	A	70dB/A
315/60R22.5*	16	154/148	L	13.0	C	A	70dB/A
315/70R22.5	16	154/150	L	14.0	C	A	70dB/A
315/70R22.5	18	156/150	L	14.0	C	A	70dB/A
315/80R22.5	20	156/150	L	15.0	C	A	70dB/A
315/80R22.5	22	158/150	L	15.0	C	A	70dB/A

* These sizes are available in OH-107+

Regrooving Guidelines



Size	D: Regrooving Depth	W: Regrooving Width
	mm	mm
10.00R20	2.5	7.0 - 8.0
11R22.5	2.5	7.0 - 8.0
12R22.5	2.5	7.0 - 8.0
255/70R22.5	2.5	6.0 - 7.0
275/70R22.5	2.5	6.0 - 7.0
295/60R22.5	2.5	9.0 - 10.0
295/80R22.5	2.5	7.0 - 8.0
315/60R22.5	2.5	9.0 - 10.0
315/70R22.5	2.5	8.0 - 9.0
315/80R22.5	2.5	8.0 - 9.0