



M+S




# OH - 112


All position tyre for regional applications



Specially designed shoulders help in preventing heel & toe wear ensuring longer life.



Optimal placement of sipes deliver improved traction and grip, thereby reducing braking distance both in dry and wet conditions.



Versatile tread design with stepped ribs ensure improved handling and driving stability.

OH - 112



Size	PR	Load Index	Speed Symbol	Tread Depth			
				mm			
7.00R16	12	117/116	L	13.0	D	B	68dB/A
7.50R16	14	122/118	L	13.5	D	B	68dB/A
8.25R16	16	132/130	L	14.0	D	B	68dB/A
9.5R17.5	14	129/127	L	14.0	D	B	68dB/A
9.5R17.5	18	143/141	J	14.0	D	B	68dB/A
215/70R17.5	12	126/124	M	12.0	D	B	68dB/A
215/75R17.5	12	126/124	M	14.0	D	B	68dB/A
215/75R17.5	16	135/133	K	14.0	D	B	68dB/A
225/80R17.5	14	123/122	L	13.0	D	B	68dB/A



## Regrooving Guidelines

Size	D: Regrooving Depth	W: Regrooving Width
	mm	mm
7.00R16	2.5	5.6 - 6.0
7.50R16	2.5	5.6 - 6.0
8.25R16	2.5	6.0 - 7.0
9.5R17.5	2.5	7.0 - 8.0
215/70R17.5	2.5	7.0 - 8.0
215/75R17.5	2.5	7.0 - 8.0
225/80R17.5	2.5	7.0 - 8.0