






OH - 115


All position tyre for regional applications



Five rib pattern maximizes surface contact and bears load evenly.




Unique shoulder design and Sipes on center ribs offer enhanced wet braking and steering.



Stone ejectors on each groove prevent retention of stones, hence ensuring better traction and grip.



Size	PR	Load Index	Speed Symbol	Tread Depth			
				mm			
215/75R17.5	12	126/124	M	12.0	D	B	70dB/A
215/75R17.5	14	128/126	M	12.0	D	B	70dB/A
215/75R17.5	16	135/133	K	12.0	D	B	70dB/A
215/75R17.5	18	143/141	J	12.0	D	B	70dB/A
225/75R17.5	12	129/127	M	13.0	D	B	70dB/A
235/75R17.5	14	132/130	M	13.0	D	B	70dB/A
235/75R17.5	16	135/133	K	13.0	D	B	70dB/A
235/75R17.5	18	143/141	J	13.0	D	B	70dB/A
245/70R17.5	16	136/134	M	13.0	D	B	70dB/A
245/70R17.5	18	143/141	J	13.0	D	B	70dB/A
245/70R19.5	16	136/134	L	15.0	D	B	70dB/A



Regrooving Guidelines

Size	D: Regrooving Depth	W: Regrooving Width
	mm	mm
215/75R17.5	2.5	7.0 - 8.0
225/75R17.5	2.5	7.0 - 8.0
235/75R17.5	2.5	7.0 - 8.0
245/70R17.5	2.5	7.0 - 8.0
245/70R19.5	2.5	7.0 - 8.0

OH - 115