



M+S



OH - 117


All position tyre for regional applications



Optimized mold profile to resist the uneven wear.



Unique shoulder design and sipes on center ribs offer enhanced wet braking and steering.




Stone ejectors on each groove prevent retention of stones, hence ensuring better traction and grip.

OH-117



Size	PR	Load Index	Speed Symbol	Tread Depth			
				mm			
7.00R16	14	118/114	L	11.0	C	B	73dB/B
7.50R16	14	122/118	L	11.0	C	B	73dB/B
7.50R16	16	124/120	L	11.0	C	B	73dB/B
8.25R16	16	132/130	L	12.5	C	B	73dB/B
8.25R16	18	134/129	K	12.5	C	B	73dB/B
9.5R17.5	18	143/141	J	14.5	D	C	73dB/B
215/75R17.5	16	135/133	L	13.0	C	B	73dB/B
225/80R17.5	14	123/122	L	12.0	C	B	73dB/B
11.00R20	16	150/146	K	15.0	D	B	73dB/B
11R22.5	16	148/145	M	15.0	D	B	73dB/B



Regrooving Guidelines

Size	D: Regrooving Depth	W: Regrooving Width
	mm	mm
7.00R16	2.5	5.0 - 6.0
7.50R16	2.5	5.0 - 6.0
8.25R16	2.5	5.0 - 6.0
9.5R17.5	2.5	7.0 - 8.0
215/75R17.5	2.5	7.0 - 8.0
225/80R17.5	2.5	7.0 - 8.0
11.00R20	2.5	7.0 - 8.0
11R22.5	2.5	7.0 - 8.0