

OH - 201


All position tyre for mixed service applications



Lugs on shoulders withstand impacts and enhance traction performance in both dry and wet conditions.



Special Zigzag tread design that offers extra-ordinary resistance against chipping and cutting in off road conditions.



Deeper tread delivers longer mileage and wider grooves help in effective water evacuation.



Size	PR	Load Index	Speed Symbol	Tread Depth				71dB/A
				mm				
7.50R16	14	122/118	L	13.5	D	B		71dB/A
8.25R16	16	132/130	L	13.5	D	B		71dB/A
10.00R20	16	147/143	L	18.0	D	B		71dB/A
10.00R20	18	149/145	J	18.0	D	B		71dB/A
11.00R20	16	150/146	K	16.0	D	B		71dB/A
11.00R20	18	152/149	K	16.0	D	B		71dB/A
12.00R20	18	154/150	K	17.0	D	B		71dB/A
11R22.5	16	148/145	L	16.0	D	B		71dB/A
295/80R22.5	16	152/148	M	17.0	D	B		71dB/A
295/80R22.5	18	154/150	K	17.0	D	B		71dB/A
315/80R22.5	20	156/150	L	15.0	D	B		73dB/B
325/95R24	22	162/160	K	19.0	D	B		71dB/A



Regrooving Guidelines

Size	D: Regrooving Depth	W: Regrooving Width
	mm	mm
7.50R16	2.5	3.0 - 4.0
8.25R16	2.5	6.0 - 7.0
10.00R20	2.5	6.0 - 7.0
11.00R20	2.5	7.0 - 8.0
12.00R20	2.5	7.0 - 8.0
11R22.5	2.5	7.0 - 8.0
295/80R22.5	2.5	7.0 - 8.0
315/80R22.5	2.5	7.0 - 8.0
325/95R24	2.5	7.0 - 8.0