




OH - 311




M+S



OH - 311

Drive axle tyre for regional applications



Creative design of 5 Lug pattern built for firm grip and cornering ability.



Open shoulder design that ensures quicker evacuation of water delivering good road grip.



Deeper and wider grooves increases mileage and enhances service life.



Size	PR	Load Index	Speed Symbol	Tread Depth			
				mm			
9.5R17.5	14	129/127	L	14.0	E	C	70dB/A
9.5R17.5	18	143/141	J	14.0	E	C	70dB/A
215/75R17.5	14	128/126	M	13.0	E	C	70dB/A
215/75R17.5	16	135/133	K	13.0	E	C	70dB/A
225/75R17.5	12	129/127	M	15.0	E	C	70dB/A
235/75R17.5	14	132/130	M	13.0	E	C	70dB/A
235/75R17.5	18	143/141	J	13.0	E	C	70dB/A
245/70R19.5	16	136/134	L	15.0	E	C	71dB/A
315/60R22.5*	16	154/148	L	18.0	E	C	75dB/B

* This size is available in OH-311+



Regrooving Guidelines

Size	D: Regrooving Depth	W: Regrooving Width
	mm	mm
9.5R17.5	2.5	7.0 - 8.0
215/75R17.5	2.5	7.0 - 8.0
225/75R17.5	2.5	7.0 - 8.0
235/75R17.5	2.5	7.0 - 8.0
245/70R19.5	2.5	7.0 - 8.0
315/60R22.5	2.5	7.0 - 8.0