

FG88™



Steer axle tyre designed to ensure resistance to tears and lacerations and mileage in construction sites.

Lower operating temperatures promote tyre integrity and retreadability.

<p>Robust circumferential ribs, rounded contour and an optimized tread groove profile</p> <p>High resistance to lacerations</p>	<p>Large tread width</p> <p>Long tyre life and mileage</p>	<p>Stone ejectors at the bottom of the central groove</p> <p>Stone trapping and casing damages prevention</p>	<p>Zig-zag longitudinal grooves and wide transversal shoulder grooves</p> <p>Grip performance on any surface</p>
---------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------

SIZE	LOAD INDEX / SPEED CODE	MARKING						
13 R 22.5	156/150 K	M+S	D	B	A	70dB	✓	
315/80 R 22.5	156/150 K	M+S	D	B	B	72dB	✓	

INDEX	PROMETEAON: TYRE SOLUTIONS FOR PROFESSIONALS	KEY FIGURES (2022 DATA)	RANGE OVERVIEW	UNIQUE INNOVATIVE TECHNOLOGICAL PLATFORM	ABBREVIATIONS AND SYMBOLS EXPLANATION	FUEL EFFICIENCY	VERSATILITY	WINTER	COACH	URBAN	CONSTRUCTION	QUARRY & MINE	SPECIAL USE	PERFORMANCE TYRES	OTHER PRODUCTS	TYRE MARKINGS	LOAD AND SPEED TABLES	NEW EU TYRE LABELLING REGULATION	INFLATION PRESSURE	STORAGE IN A ROW ON PALLETS
-------	----------------------------------------------	-------------------------	----------------	------------------------------------------	---------------------------------------	-----------------	-------------	--------	-------	-------	--------------	---------------	-------------	-------------------	----------------	---------------	-----------------------	----------------------------------	--------------------	-----------------------------